

Instruction

The DNAKE C112 enables you to make the video call with villa entrance door, and open the door remotely from indoor monitor or mobile APP. It also makes an easy integration with SIP devices.

DNAKE C112 (Surface Mounting)



Key Features

- Compact Design
- 2MP, 1080P HD Camera, digital WDR
- H.265 Video Codec
- Motion Detection
- Tamper Alarm
- Optional IC card reader, WIFI and Bluetooth

Physical

- | | |
|---|---|
| • System: Linux | • Reset Button:1 |
| • Front Panel: Plastic | • RS485 Port: 1 |
| • Power Supply: PoE (802.3af) or DC 12V/2A | • Relay Out: 1 |
| • Camera: 2MP, CMOS, WDR | • Input: 2 |
| • Indicator Light: 3 | • IP Rating: IP65 |
| • Wiegand Port: Support | • Installation: Surface Mounting |
| • Wi-Fi: IEEE802.11 b/g/n, @2.4GHz (Optional) | • Surface Mounting DIM: 130 x 50 x 28 mm |
| • Bluetooth: Bluetooth (Optional) | • Working Temperature: -40°C to +55°C |
| • TF Card Slot: 1 | • Storage Temperature: -40°C to +70°C |
| • Ethernet Port: 1 x RJ45, 10/100 Mbps adaptive | • Working Humidity: 10% to 90% (non-condensing) |
| • Door Entry: IC (13.56MHz) card (Optional) | |



Datasheet

Audio

- Audio Codec: G.711
- Echo Cancellation
- DTMF: RFC2833
- Microphone: Built-in microphone
- Speaker: Built-in speaker

Networking

- Protocol: SIP, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP

Video

- Video Codec: H.264, H.265
- Video Resolution: 1920 x 1080
- Viewing Angle: 110° (H) / 60° (V) / 125° (D)
- Max. Image Transfer Rate: 1080p – 25fps
- Light Compensation: LED white light

